



CS-100 is a practical and economical conference discussion system, elegant appearance, convenient installation, simple operation, widely apply to boardrooms, business meetings, educational institutions, hotels, conference rental, system reconstruction, etc.

## Product Specification

- EIA standard 1U metal rack receiver chassis;
- Equipped with handle, easy for lift or move.

Main Frame Size	EIA Standard 1U
Mains Voltage	100V-240V AC 50/60Hz 50W
Current Consumption	45W
Frequency Response	55Hz-17KHz ±2dB
S/N	>90dB
Static Power	500mW
Output Power	15W/12V(Each Channel)
Distortion(T.H.D)	<0.3%
Audio Input	RCA Input: -9dBV(f=1KHz,THD<0.3%)
Audio Output	XLR Output: -10dBV Unbalanced Line Output (6.3mm jack): -15dBV RCA Output: -3dBV
Chairman/Delegate Unit Interface	Anti drop 9P aviation plug
Dimension(mm)	410(W)x43(H)x206(D)
Weight(kg)	2.3kg



**CS-100M**  
Central Controller



**CS-100C**  
Chairman Unit



**CS-100D**  
Delegate Unit

- Advanced conferencing technology, compliant with ICE60914.
- Unidirectional condenser microphone for high quality sound pickup.
- Anti-drop aviation cable, hand in hand connection way, simple connection, reliable and convenient for set up.
- Priority bottom to switch off the speaking unit.
- With illuminated ring to indicate the working status;
- Black or silver for selection.

Mains Voltage	DC12V
Polar Pattern	Cardioid Condenser
Current Consumption	110mA
Frequency Response	65Hz-18KHz
S/N	>90dB
Distortion(T.H.D)	<0.7%
Sensitivity	-20dBV/Pa
Chairman/Delegate Unit Interface	Anti drop 9P aviation plug
Microphone Length (Selectable)	340mm/420mm(default) /480mm
Tabletop(without microphone)(mm)	105(W)x43(H) x 150(D)
Weight(g)	780g
Color	Nickel black

- Advanced conferencing technology, compliant with ICE60914.
- Unidirectional condenser microphone for high quality sound pickup.
- Anti-drop aviation cable, hand in hand connection way, simple connection, reliable and convenient for set up.
- Priority bottom to switch off the speaking unit.
- With illuminated ring to indicate the working status;
- Black or silver for selection.

Mains Voltage	DC12V
Current Consumption	110mA
Polar Pattern	Cardioid Condenser
Frequency Response	65Hz-18KHz
Distortion(T.H.D)	<0.7%
Sensitivity	-20dBV/Pa
Chairman/Delegate Unit Interface	Anti drop 9P aviation plug
Microphone Length (Selectable)	340mm/420mm(default) /480mm
Tabletop(without microphone)(mm)	105(W)x43(H) x 150(D)
Weight(g)	780g
Color	Nickel black

## Key Features

### Clear Sound Quality

- Unidirectional condenser microphone for high quality sound pickup.
- Equipped with auto-gain audio process circuit, effective prevent the feedback.
- Built-in high performance processor, enable auto-process system gain, control feedback.

### Flexible Speech

- Active 1/3/6 microphones in a time, AUTO speaking mode, chairman unit has the priority to override all delegate units.

### Anti-Interference

- Special 9-pin aviation connection cable, effectively minimize the interference.

### Flexible Expansion

- Can connect up to 60 microphone units.
- Audio input function, enable to connect to the external audio equipment.
- Connecting the telephone coupler can apply to the remote telephone conference directly.

## Application:

