

# CS-302M | Central Controller



## Description

CS-302 is a simple and affordable conference discussion system. With exquisite design, focusing on application of various conferences, the newly developed sound activate mode, the participants don't need operating manually, just speaking to microphones directly, the microphone unit can be started to speak, simple to use, fully applicable to the various conference locations.

## Product Specification

Chassis Pecifications:	EIA Standard Rack 1U
Supply Voltage:	90-264V AC or 127-370V AC,47-63Hz
Static Power Consumption:	6W
Rated Power:	75W/24V
Maximum Power:	100W/24V
XLR Balances Carnon Maximum Output Level:	14,6dBu
Maximum output level of the 6.35mm balance socket:	14.6dBu
RCA lotus socket maximum output level:	9.8 dBu
RCA lotus socket maximum input level:	3.2 dBu
Conference Unit Extension:	Anti drop 9P aviation plug x 1 Network port (female) x1
Video Input Port:	BNC x 4
Video Output Port:	BNC x 1
Video Interface Impedance:	75Ω
9 pin serial port control interface:	Db9 Female plug x 1
Rs-232 control protocol interface:	5P Phoenix terminal X 1
Rs-422 control protocol interface:	5P Phoenix terminal X 1
Dante interface:	Rj45x1
Audio output:	XLRM x 1, 6.35mm jack x 1, RCA x 1
Audio input:	RCA x 1
Screen type:	OLED
Key mode:	Touch style
Weight:	About 2.3kg
Dimension (mm):	410 (W)×206 (D)×43 (H)